




SHELL 30

WL, LED Indoor surface-mounted wall light, 3000K, white

The elegant SHELL wall light is a combination of aluminium and acrylic glass. The dimmable wall light is available in two sizes. The one or two long-life LEDs each have output of 12W, and provide the required luminous intensity. The wall light has a strong design and can be directly connected to the 230V mains supply as it has an integrated LED driver.



TECHNICAL DATA

Item no.	1000423
Number of different light outlets	1
IP Code	IP20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	TRAILING_EDGE
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	1300 mA
Safety class	I
Wattage	50 W
Number of luminaires at LS B16A	50
Number of luminaires at LS C16A	50
Level of inrush current	5 A
Duration of inrush current	300 µs
Stroboscopic effect (SVM)	0.03
Lumen	5650 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
Color	white

Light Source

780750	
--------	---

CRI	90
LXXBXX data	L70B50
Service life	50000 h
Light distribution	symmetric
Light outlet	direct
Light outlet 2	indirect
Risk Group	1
Width	28.6 cm
Height	7 cm
Depth	16 cm
Net weight	1.852 kg
Gross weight	2.118 kg
BIG WHITE Page	365