




FRAME LED 230V CURVE

LED Indoor recessed wall light, 2700K


Our FRAME 240V LED series is a space-saving lighting solution for recessed wall installation. The LED version is equipped with a long-life LED, and is available with a warm white light colour. The optionally available accessories include installation boxes and flush-mounted frames. The electrical connection is made directly to the 230V mains voltage supply. This luminaire contains built-in LED lamps.



TECHNICAL DATA

| | |
|---------------------------------|-------------------|
| Item no. | 1000574 |
| IP Code | IP 20 |
| Assembly | Recessed |
| Assembly details | Wall |
| Primary nominal voltage | 100-240V ~50/60Hz |
| Secondary power / voltage | 350 mA |
| Safety class | I |
| Wattage | 3 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 30 °C |
| Operating efficiency (LOR) | 0,486 |
| Number of luminaires at LS B16A | 64 |
| Number of luminaires at LS C16A | 94 |
| Level of inrush current | 15 A |
| Duration of inrush current | 300 µs |
| Stroboscopic effect (SVM) | 0.4 |
| Lumen | 140 lm |
| Colour temperature | 2700 Kelvin |
| Color | white |
| CRI | 90 |
| LXXBXX data | L70B50 |
| Service life | 60000 h |

Light Source

| | |
|--|---|
| |  |
|--|---|

Accessories

| | |
|--------|--|
| 112781 | MOUNTING BOX , for FRAME BASIC, FLAT FRAME BASIC, FLAT FRAME CURVE and FRAME CURVE |
| 112780 | FLUSH-MOUNTED , FRAME, for FRAME BASIC, FLAT FRAME BASIC, FLAT FRAME CURVE and FRAME CURVE |

| | |
|---------------------|----------|
| Risk Group | 1 |
| Length | 9 cm |
| Width | 9 cm |
| Depth | 5.5 cm |
| Net weight | 0.255 kg |
| Gross weight | 0.314 kg |
| Shape of cut-out | square |
| Installation length | 7.2 cm |
| Installation width | 8 cm |
| Installation depth | 6.5 cm |
| BIG WHITE Page | 239 |