




FRAME LED 230V CURVE

LED Indoor recessed wall light, 2700K

Our FRAME 240V LED series is a space-saving lighting solution for recessed wall installation. The LED version is equipped with a long-life LED, and is available with a warm white light colour. The optionally available accessories include installation boxes and flush-mounted frames. The electrical connection is made directly to the 230V mains voltage supply. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.	1000575
IP Code	IP 20
Assembly	Recessed
Assembly details	Wall
Primary nominal voltage	100-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	3 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Operating efficiency (LOR)	0,486
Number of luminaires at LS B16A	64
Number of luminaires at LS C16A	94
Level of inrush current	15 A
Duration of inrush current	300 µs
Stroboscopic effect (SVM)	0.4
Lumen	140 lm
Colour temperature	2700 Kelvin
Color	grey
CRI	90
LXXBXX data	L70B50
Service life	60000 h

Light Source

	
--	-----------------------------------------------------------------------------------

Accessories

112781	MOUNTING BOX , for FRAME BASIC, FLAT FRAME BASIC, FLAT FRAME CURVE and FRAME CURVE
112780	FLUSH-MOUNTED , FRAME, for FRAME BASIC, FLAT FRAME BASIC, FLAT FRAME CURVE and FRAME CURVE

Risk Group	1
Length	9 cm
Width	9 cm
Depth	5.5 cm
Net weight	0.256 kg
Gross weight	0.317 kg
Shape of cut-out	square
Installation length	7.2 cm
Installation width	8 cm
Installation depth	6.5 cm
BIG WHITE Page	239