




Q-LINE CL

LED Indoor surface-mounted ceiling light, 1m, BAP, black, 3000K


The Q-LINE ceiling light is optionally available with a white, black, or silver-grey luminaire housing. It is also available with a pure white or warm white LED, and different dimensions. Its high luminance and UGR value of less than 10 make the Q-Line luminaire suitable for workstations. Thanks to the TRIAC dimmable LED driver, the luminaire can be directly connected to the 230 Volt mains voltage supply.



TECHNICAL DATA

| | |
|-----------------------------------|-------------------|
| Item no. | 1000686 |
| Number of different light outlets | 1 |
| IP Code | IP 20 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 900 mA |
| Safety class | I |
| Wattage | 46 W |
| Level of inrush current | 30 A |
| Duration of inrush current | 40 μ s |
| Stroboscopic effect (SVM) | 0.16 |
| Lumen | 2100 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 30 ° |
| Color | black |
| CRI | 90 |
| UGR \leq | 10 |
| LXXBXX data | L70B50 |
| Service life | 25000 h |

Light Source

| | | | |
|--------|---|--------------------|----------------|
| 916433 |  | Light distribution | axis symmetric |
| | | Light outlet | direct |
| | | Length | 100 cm |
| | | Width | 6 cm |
| | | Height | 6 cm |
| | | Net weight | 2.266 kg |
| | | Gross weight | 2.7 kg |
| | | BIG WHITE Page | 253 |