




## PANEL 60 round

LED Indoor surface-mounted ceiling light, silver-grey, 4000K


The LED PANEL 60 comes with several different light and housing colours, and provides a modern and space-saving solution for an efficient type of basic lighting. The high degree of luminous flux provides a pleasant, homogeneous and glare-free lighting feeling. The electrical connection is made directly to the 230V mains voltage supply. This luminaire contains built-in LED lamps.



## TECHNICAL DATA

Item no.	1000786
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	40
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	1000 mA
Safety class	I
Wattage	42 W
Level of inrush current	9 A
Duration of inrush current	50 $\mu$ s
Stroboscopic effect (SVM)	0.04
Lumen	3350 lm
Colour temperature	4000 Kelvin
Beam angle	110 °
Color	grey
CRI	80
UGR $\leq$	22
LXXBXX data	L70B50
Service life	30000 h

Light Source

916481		Light distribution	rotational symmetric
		Light outlet	direct
		Height	5.5 cm
		Diameter	60 cm
		Net weight	4.525 kg
		Gross weight	5.825 kg
		BIG WHITE Page	274