




ALAMEA

recessed ceiling light, LED, 4000K, white, 29,4W

The ALAMEA recessed ceiling light for commercial applications and applications needing clear light properties. Available with a black or white housing, the ALAMEA is equipped with a powerful 29.4 Watt LED. The LED insert, which is available in two light colours, is telescopic and adjustable, and can therefore be flexibly directed. A suitable LED constant current driver is required to operate the recessed fitting. This luminaire has a built-in LED module.



TECHNICAL DATA

Item no.	1000793
Rotating or tilting	tiltable
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	700 mA
Safety class	III
Lumen	2750 lm
Colour temperature	4000 Kelvin
Color	white
CRI	80
LXXBXX data	L70B50
Service life	35000 h
Light distribution	axis symmetric
Light outlet	direct
Length	24.6 cm
Width	15.6 cm
Height	11.3 cm
Net weight	2.216 kg
Gross weight	2.474 kg
Shape of cut-out	square
Installation length	22.5 cm

Installation width	13 cm
Installation depth	11.3 cm

Accessories

1001114	LED driver , 700mA, 40-W, dimmable
464168	LED DRIVER , 40W, 700-mA, incl. strain relief
464174	LED DRIVER , 40W, 700-mA, incl. strain relief, dimmable
464032	TCI LED DRIVER , 50VA, 350-1050mA, dip switch, incl. strain relief, DALI dimmable