




## Q-LINE PD

LED indoor pendant, 2m, BAP, white, 4000K


The Q-LINE ceiling light is optionally available with a white, black, or silver-grey luminaire housing. It is also available with a pure white or warm white LED, and different dimensions. Its high luminance and UGR value of less than 10 make the Q-Line luminaire suitable for workstations. Thanks to the TRIAC dimmable LED driver, the luminaire can be directly connected to the 230 Volt mains voltage supply.



## TECHNICAL DATA

Item no.	1000935
Number of different light outlets	1
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	900 mA
Safety class	I
Wattage	93 W
Level of inrush current	30 A
Duration of inrush current	40 µs
Stroboscopic effect (SVM)	0.08
Lumen	4600 lm
Colour temperature	4000 Kelvin
Beam angle	30 °
Color	white
CRI	90
UGR ≤	10
LXXBXX data	L70B50
Service life	25000 h

## Light Source

916460		Light distribution	axis symmetric
		Light outlet	direct
		Length	200 cm
		Width	6 cm
		Height	6 cm
		Pendant length	150 cm
		Net weight	4.464 kg
		Gross weight	5.307 kg
		BIG WHITE Page	293