




DOLIX OUT QPAR51

round, white

The DOLIX OUT high-voltage recessed ceiling ring is made from aluminium and has glass protection against splashing water. Thanks to its IP65 rating, it is suitable for use outdoors and in wet rooms. The integrated GU10 high-voltage fitting means the DOLIX OUT recessed ceiling ring is ready for immediate connection to the 230V mains voltage.



TECHNICAL DATA

| | |
|-------------------------|-------------------|
| Item no. | 1001165 |
| Socket | GU10 |
| Number of sockets | 1 |
| IP Code | IP 65 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Safety class | II |
| Wattage | 50 W |
| Color | white |
| Light outlet | direct |
| Height | 11 cm |
| Diameter | 8.2 cm |
| Net weight | 0.184 kg |
| Gross weight | 0.217 kg |
| Shape of cut-out | round |
| Installation depth | 11 cm |
| Installation diameter | 6.8 cm |
| BIG WHITE Page | 235 |

Recommended lamp

| | |
|---------|--|
| 1005273 | QPAR51 GU10 , LED light, 6W 2200 2700K CRI90 36° |
| 1005079 | LED lightbulb QPAR51 , GU10, 3000K, white |
| 1005076 | LED lightbulb QPAR51 , GU10, 2700K, white |
| 1005082 | LED lightbulb QPAR51 , GU10, 4000K, white |