




AKALO 83

DL, indoor recessed ceiling light, 3000K 4200K 5700K adjustable, white


The AKALO luminaire is a recessed ceiling light for universal use indoors. The light temperature is switchable in all versions. The electrical connection is made directly to the 230V mains supply.



TECHNICAL DATA

Item no.	1001264
Number of different light outlets	1
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	120 mA
Safety class	II
Wattage	9 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	5 A
Duration of inrush current	300 µs
Stroboscopic effect (SVM)	0.01
Lumen	800/880/850 lm
Colour temperature	3000/4000/5700 Kelvin
Beam angle	90 °
Color	white
CRI	80

Light Source

916471		UGR ≤	28
		LXXBXX data	L70B50
		Service life	30000 h
		Height	6.5 cm
		Diameter	11 cm
		Net weight	0.186 kg
		Gross weight	0.243 kg
		Shape of cut-out	round
		Installation depth	7 cm
		Installation diameter	9.2 cm
		BIG WHITE Page	237