



L-LINE 60 LED

wall and ceiling light, IP44, 3000K, 820lm, silver

The L-LINE 60 wall and ceiling light is fitted with a warm-white LED module and, thanks to its 1500 lm of LED power, is the ultimate LED solution for primary room lighting. The smooth and elegant L-LINE LED is available in white, silver-grey and grey colour versions. Thanks to the integrated LED driver, the luminaire can be connected directly to the 230V mains supply.

TECHNICAL DATA

Item no.	1001300
IP Code	IP 44
Assembly	Surface
Assembly details	Wall
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	10 W
Level of inrush current	10 A
Duration of inrush current	100 µs
Stroboscopic effect (SVM)	0.3
Lumen	820 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
Color	silver
CRI	80
LXXBXX data	L70B50
Service life	30000 h
Light distribution	symmetric
Light distribution 2	symmetric
Light outlet	direct
Light outlet 2	indirect

Light Source

916534	
--------	---

Width	61.8 cm
Height	7 cm
Depth	7 cm
Net weight	1.106 kg
Gross weight	1.472 kg
BIG WHITE Page	341