




Q-LINE DALI SINGLE LED

pendant, dimmable, 1500mm, white



The Q-LINE DALI wall light is available with a choice of a white, back, or silver-grey luminaire housing. A diffuser made of acrylic glass found underneath provides glare-free lighting properties. The integrated warm-white LEDs give an output of 3200 lm. Thanks to the DALI dimmable LED driver, the luminaire can be directly connected to the 230V mains supply.



TECHNICAL DATA

Item no.	1001310
Number of different light outlets	1
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI 2
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	47 W
Rated standby power	0.16 W
Number of luminaires at LS B16A	14
Number of luminaires at LS C16A	23
Level of inrush current	40 A
Duration of inrush current	178 µs
Temperature at glass (light emission)	45 °C
Stroboscopic effect (SVM)	0.4
Lumen	3700 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
Color	white

Light Source

916631	
916371	

CRI	80
UGR ≤	28
LXXBXX data	L70B50
Service life	30000 h
Light distribution	axis symmetric
Light outlet	direct
Length	142 cm
Width	6 cm
Height	6 cm
Pendant length	200 cm
Net weight	3.568 kg
Gross weight	4.084 kg
BIG WHITE Page	293