




GLENOS

professional pendant, LED, 3000K, black, 2 m, 85W

The GLENOS pendant with a high-performance LED strip gives you a powerful, top-class LED lighting. The pendants are available in several lengths and colour variants and are fitted with a 2.50 m connection lead, which can be shortened individually. The GLENOS pendant is ready to connect to the 230 V mains supply thanks to the dimmable LED driver.



TECHNICAL DATA

| | |
|-----------------------------------|-------------------|
| Item no. | 1001406 |
| Number of different light outlets | 1 |
| IP Code | IP 20 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 1000 mA |
| Safety class | I |
| Wattage | 85 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 50 °C |
| Level of inrush current | 30 A |
| Duration of inrush current | 300 µs |
| Stroboscopic effect (SVM) | 0 |
| Lumen | 5700 lm |
| Colour temperature | 3000 Kelvin |
| Color | black |
| CRI | 80 |
| UGR ≤ | 28 |
| LXXBXX data | L70B50 |
| Service life | 35000 h |
| Light distribution | axis symmetric |

Light Source

| | |
|--------|---|
| 916482 |  |
|--------|---|

| | |
|----------------|----------|
| Light outlet | direct |
| Length | 205 cm |
| Width | 5 cm |
| Height | 7 cm |
| Pendant length | 200 cm |
| Net weight | 4.544 kg |
| Gross weight | 5.412 kg |
| BIG WHITE Page | 291 |