




## GLENOS

professional pendant, LED, 3000K, anodised aluminium, 2 m, 45W

The GLENOS pendant with a high-performance LED strip gives you a powerful, top-class LED lighting. The pendants are available in several lengths and colour variants and are fitted with a 2.50 m connection lead, which can be shortened individually. The GLENOS pendant is ready to connect to the 230 V mains supply thanks to the dimmable LED driver.



## TECHNICAL DATA

Item no.	1001408
Number of different light outlets	1
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	1000 mA
Safety class	I
Wattage	85 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	50 °C
Level of inrush current	30 A
Duration of inrush current	300 µs
Stroboscopic effect (SVM)	0
Lumen	5700 lm
Colour temperature	3000 Kelvin
Color	silver
CRI	80
UGR ≤	28
LXXBXX data	L70B50
Service life	35000 h
Light distribution	axis symmetric

## Light Source

916482	
--------	---

Light outlet	direct
Length	205 cm
Width	5 cm
Height	7 cm
Pendant length	200 cm
Net weight	4.447 kg
Gross weight	5.363 kg