


RUSTY® PATHLIGHT70

LED outdoor floor stand, rust coloured, IP55, 3000K

The direct radiating floor stands of the RUSTY series convince by their exceptional rust look. This is achieved by a special chemical treatment of the FeCSi steel used. This makes the luminaire a unique piece and an absolutely special feature wherever they are installed. With protection class IP55, it is suitable for outdoor use. As an option an earth spike as well as a connection box for safe electrical connection to the round luminaire upright, are available. Equipped with a powerful LED, the luminaire connects directly to a 230V mains voltage supply.



TECHNICAL DATA

| | |
|-----------------------------------|-------------------|
| Item no. | 1001824 |
| Number of different light outlets | 1 |
| IP Code | IP 55 |
| Impact resistance class | IK 06 |
| Impact resistance | 1 Joule |
| Assembly | Surface |
| Assembly details | Ground |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Safety class | I |
| Wattage | 8.9 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Level of inrush current | 0.35 A |
| Stroboscopic effect (SVM) | 3.3 |
| Lumen | 400 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 90 ° |
| Color | rust |
| CRI | 80 |
| LXXBXX data | L70B50 |
| Service life | 25000 h |
| Light distribution | symmetric |

Light Source

| | |
|--------|---|
| 954800 |  |
|--------|---|

Accessories

| | |
|--------|--|
| 228730 | CONNECTION BOX , 3-pin, IP68 |
| 229422 | Earth spike , galvanised steel, 50 cm |

| | |
|--------------|-----------|
| Light outlet | direct |
| Length | 15 cm |
| Width | 25 cm |
| Height | 70 cm |
| Net weight | 19.57 kg |
| Gross weight | 22.226 kg |