




NOBLO SPOT

white, 2700K, 36°, incl. 1-circuit adapter

Adjustable LED spot NOBLO with suitable adapter for the 240V 1-circuit track system. The luminaire impresses with its slim design and is therefore ideal for modern lighting concepts. The luminaire is made from aluminium and equipped with a Premium LED module.



TECHNICAL DATA

| | |
|-----------------------------------|---------------------------|
| Item no. | 1001863 |
| Number of different light outlets | 1 |
| Rotating or tilting | rotary Bar and tiltable |
| IP Code | IP 20 |
| Assembly | Surface |
| Assembly details | Track Ceiling, Track Wall |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 350 mA |
| Safety class | I |
| Wattage | 8 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 30 °C |
| Operating efficiency (LOR) | 0,8 |
| Number of luminaires at LS B16A | 128 |
| Number of luminaires at LS C16A | 160 |
| Level of inrush current | 3.5 A |
| Duration of inrush current | 120 µs |
| Stroboscopic effect (SVM) | 0.4 |
| Lumen | 620 lm |
| Colour temperature | 2700 Kelvin |

Light Source

| | |
|--------|---|
| 916369 |  |
|--------|---|

| | |
|--------------|----------|
| Beam angle | 36 ° |
| Color | white |
| CRI | 80 |
| LXXBXX data | L70B50 |
| Service life | 30000 h |
| Risk Group | 1 |
| Length | 10.5 cm |
| Height | 10.7 cm |
| Diameter | 5 cm |
| Net weight | 0.245 kg |
| Gross weight | 0.325 kg |