


## MEDO 30 EL

LED indoor recessed ceiling light, frameless version, white, 3000/4000K

The recessed version of the MEDO series fits into every room concept seamlessly thanks to its understated design. The MEDO Frameless combines with the ceiling in a charming way. The light colour can be easily switched between 3000K and 4000K prior to installation using a switch. The integrated premium LED module provides an even lighting effect. Supplemented by an additional driver, the TRIAC recessed variant becomes dimmable and can be integrated in DALI systems.



## TECHNICAL DATA

Item no.	1001901
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	350 mA
Safety class	III
Wattage	14 W
Maximum ambient temperature	40 °C
Lumen	1500/1600 lm
Colour temperature	3000/4000 Kelvin
Beam angle	105 °
Color	white
CRI	80
UGR ≤	25
LXXBXX data	L70B50
Service life	25000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Height	9.5 cm
Diameter	28 cm
Net weight	1.272 kg

Light Source

916562	
--------	---

Accessories

1002423	LED driver MEDO 300 , dimmable DALI/1-10V
1007229	LED driver 25W 150-700-mA DALI TOUCH
1007228	LED Driver 20W 350mA dimmable
1007225	LED Driver 20W 350mA

Gross weight	1.826 kg
Shape of cut-out	round
Installation depth	13 cm
Installation diameter	29 cm
BIG WHITE Page	170