


MEDO 40 EL

LED indoor recessed ceiling light, frame version, white, 3000/4000K

The MEDO FRAME variants round off the recessed lights in the MEDO series. The MEDO FRAME lights blend into any room perfectly, just like the frameless versions. Understated yet still powerful, they provide bright illumination. Supplemented by an additional driver, the TRIAC recessed variant becomes dimmable and can be integrated in DALI systems.



TECHNICAL DATA

Item no.	1001906
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	700 mA
Safety class	III
Wattage	28 W
Maximum ambient temperature	40 °C
Lumen	3100/3300 lm
Colour temperature	3000/4000 Kelvin
Beam angle	105 °
Color	white
CRI	80
UGR ≤	25
LXXBXX data	L70B50
Service life	25000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Height	10.2 cm
Diameter	40 cm
Net weight	2.46 kg

Light Source

916346	
--------	---

Accessories

1006120	LED driver , 40W 700/900/1000mA
1005446	LED driver , 40W 700mA PHASE
1004781	LED driver , 21-29.5W 500/600/700mA
1006196	LED driver , 40W 700mA DALI dimmable with RF interface LED driver white DALI
1002424	LED driver MEDO 400 , dimmable DALI/1-10V

Gross weight	3.39 kg
Shape of cut-out	round
Installation depth	13 cm
Installation diameter	39 cm
BIG WHITE Page	171