




NEW TRIA angular

LED indoor recessed ceiling light, brushed aluminium, 1800-3000K 7.2W

The square, 240V version of our popular NEW TRIA LED recessed fitting series is available with white, black or brushed aluminium housings. The swivelling range of this recessed spotlight ensures that you can individually focus the light beam. The LEDs can be adjusted to the required light colour using the innovative Dim to Warm technology. Specifically designed for a hole diameter of 68 mm, the NEW TRIA 68 recessed fitting is supplied ready for direct connection to the 230V alternating current. The scope of delivery of the product includes clip and leaf springs for convenient adaptation to the respective fitting situation.



TECHNICAL DATA

Item no.	1001993
Rotating or tilting	tiltable
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Dim-to-Warm, Leading edge, trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	II
Wattage	7.3 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	2 A
Duration of inrush current	40 µs
Stroboscopic effect (SVM)	0.02
Lumen	47-470 lm
Colour temperature	1800-3000 Kelvin
Beam angle	38 °
Color	aluminium
CRI	95
LXXBXX data	L70B50

Light Source

916436	
--------	---

Service life	30000 h
Risk Group	1
Length	8.2 cm
Width	8.2 cm
Height	3.5 cm
Net weight	0.239 kg
Gross weight	0.289 kg
Shape of cut-out	round
Installation depth	4 cm
Installation diameter	7 cm