
# Specialist • Lighting • Vendor








## HELIA 30 PD

LED indoor pendant, soft gold, 3000K, surface-mounted version

With the HELIA 30 you have a pendant with a purist and clear design. This luminaire is available in soft gold, black, white and brushed copper. A 7.5W warm-white premium LED is integrated, this is supplied from the built-in constant current driver. The luminaire is delivered with a 1.5 m connection lead. This means the luminaire is ready for direct connection to the 230V mains supply.




#### **TECHNICAL DATA**

Item no.	1002172
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	9.2 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Level of inrush current	10 A
Duration of inrush current	40 µs
Stroboscopic effect (SVM)	0.01
Lumen	620 lm
Colour temperature	3000 Kelvin
Beam angle	40 °
Color	gold
CRI	90
LXXBXX data	L70B50
Service life	30000 h

# Specialist • Lighting • Vendor



### **Light Source**



Length	60 cm
Diameter	3 cm
Pendant length	150 cm
Net weight	0.81 kg
Gross weight	1.095 kg