



ARLINA 130

Indoor LED surface-mounted wall light alu 3000K

You get particularly pleasant light for your living areas and business premises from the integrated Premium LED in the ARLINA 130 surface-mounted wall light. With a CRI value of greater than or equal to 80, the ARLINA 130 surface-mounted wall light is very suitable for true-colour lighting of sales or office premises. This surface-mounted wall light is sustainable and low-maintenance thanks to the anticipated service life of 30,000 hours.

TECHNICAL DATA

Item no.	1002240
IP Code	IP20
Assembly	Surface
Assembly details	Wall
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	31 W
Minimum ambient temperature	-25 °C
Maximum ambient temperature	35 °C
Operating efficiency (LOR)	0,75
Number of luminaires at LS B16A	31
Number of luminaires at LS C16A	49
Level of inrush current	13.6 A
Duration of inrush current	220 µs
Stroboscopic effect (SVM)	0.4
Lumen	2400 lm
Colour temperature	3000 Kelvin
Color	aluminium
CRI	80
LXXBXX data	L70B50
Service life	50000 h

Light Source

916544	
--------	---

Risk Group	1
Length	128 cm
Width	6.8 cm
Height	6 cm
Net weight	3.581 kg
Gross weight	4.416 kg
BIG WHITE Page	371