




DIO FLEX PLATE LED

LED Indoor surface-mounted wall light, black, 4000K

Adjustable 240V display fitting for wall mounting of the DIO FLEX PLATE series, whereby the canopy and lamp head are connected via a flexible arm. Because of the switch that is fitted, the individually adjustable luminaire is suitable for many applications. The luminaire is connected directly to the 230V mains supply. An LED version is available as an alternative.



TECHNICAL DATA

| | |
|-----------------------------|-------------------|
| Item no. | 1002432 |
| IP Code | IP 20 |
| Assembly | Surface |
| Assembly details | Wall |
| Primary nominal voltage | 100-240V ~50/60Hz |
| Secondary power / voltage | 350 mA |
| Safety class | I |
| Wattage | 1.9 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 45 °C |
| Stroboscopic effect (SVM) | 0 |
| Lumen | 100 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 45 ° |
| Color | black |
| CRI | 80 |
| LXXBXX data | L70B50 |
| Service life | 30000 h |
| Length | 49.8 cm |
| Diameter | 9 cm |
| Net weight | 0.507 kg |
| Gross weight | 0.583 kg |

Light Source

| | | | |
|--------|--|----------------|-----|
| 916340 |  The logo consists of a small square with the letters 'A' and 'G' stacked vertically on the left, and a larger orange arrow pointing to the right containing the letter 'F' on the right. | BIG WHITE Page | 387 |
|--------|--|----------------|-----|