




DASAR® 270

Outdoor LED inground fitting, 3000K, round, IP67, asymmetrical beam

The accessible high-voltage inground light DASAR® 270 Outdoor LED inground light 3000K round IP67 asymmetric distribution convinces with its stainless steel screen and glass cover in a partial satin finish. Thanks to the rotatable and pivoting GU10 fitting, you can direct the light cone individually. And thanks to its IP 65 / IP 67 protection class, it is optimally suited for outdoor areas. The housing is made of high-quality aluminium and 316 stainless steel. When will you test out the benefits of SLV's impressive outdoor lights?



TECHNICAL DATA

Item no.	1002893
IP Code	IP 65 / IP 67
Impact resistance class	IK 08
Impact resistance	5 Joule
Assembly	Recessed
Assembly details	Ground
Number of through-wires	60
Mechanical loading	2 t
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	30 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Level of inrush current	30 A
Duration of inrush current	40 µs
Temperature at glass (light emission)	36 °C
Lumen	2000 lm
Colour temperature	3000 Kelvin
Color	stainless steel
CRI	80
LXXBXX data	L70B50

Light Source

916518	
--------	---

Service life	50000 h
Light distribution	asymmetric
Light outlet	direct
Risk Group	1
Height	20.3 cm
Diameter	27 cm
Net weight	5.275 kg
Gross weight	6.195 kg
Shape of cut-out	round
Installation depth	19.9 cm
Installation diameter	25 cm
BIG WHITE Page	841