




DASAR® 270

Outdoor LED inground fitting, 4000K, round, IP67, symmetrical beam

The high-voltage DASAR® 270 Outdoor LED recessed ground light 4000K round IP67 symmetric distribution can be walked on, and impresses with its stainless steel screen and glass cover in a partial satin finish. And last but not least, it is the LED lifespan of 50,000 hours that makes the outdoor recessed LED ground light a long-lasting companion. See the outdoor lights in action and let yourself be impressed by a stunning lighting experience.



TECHNICAL DATA

Item no.	1002898
IP Code	IP 65 / IP 67
Impact resistance class	IK 08
Impact resistance	5 Joule
Assembly	Recessed
Assembly details	Ground
Number of through-wires	60
Mechanical loading	2 t
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	30 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Level of inrush current	30 A
Duration of inrush current	40 µs
Temperature at glass (light emission)	35 °C
Lumen	2600 lm
Colour temperature	4000 Kelvin
Beam angle	38 °
Color	stainless steel
CRI	80

Light Source

916550	
--------	---

Accessories

1002899	Grill Diffusor for DASAR® 270 Outdoor , LED in-ground fitting with symmetrical beam
---------	---

LXXBXX data	L70B50
Service life	50000 h
Light distribution	symmetric
Light outlet	direct
Risk Group	1
Height	20.3 cm
Diameter	27 cm
Net weight	5.936 kg
Gross weight	6.843 kg
Shape of cut-out	round
Installation depth	19.9 cm
Installation diameter	25 cm
BIG WHITE Page	841