




## RETRATO

Indoor LED surface-mounted wall light, 3000K, white


RETRATO WL in which the canopy and the lamp head are connected via an arm together with two joint pieces. The incorporated LEDs make it possible to provide your exhibits with gentle illumination by UV-free LED light without significant heat dissipation. Both assembled joints ensure that the lamp is aligned perfectly. The luminaire is available in several housing colours. Thanks to the assembled LED power supply, the electrical connection of the luminaire is made directly via 230V mains power supply. This luminaire contains built-in LED lamps.



## TECHNICAL DATA

Item no.	1002960
IP Code	IP 20
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	11 W
Maximum ambient temperature	35 °C
Level of inrush current	2 A
Duration of inrush current	50 µs
Stroboscopic effect (SVM)	0.04
Lumen	750 lm
Colour temperature	3000 Kelvin
Color	white
CRI	90
LXXBXX data	L70B50
Service life	30000 h
Length	30 cm
Width	5.2 cm

Light Source

916523		Height	20.1 cm
		Net weight	0.542 kg
		Gross weight	0.887 kg