




FERA 25 CL DALI

Indoor LED surface-mounted ceiling light, white


The FERA 25 240V LED ceiling light impresses with its simple, clear design and high luminosity. The built-in LEDs produce outstanding lumen output. Thus, the fitting can be used for general room lighting. Thanks to the built-in LED driver, the light is ready for direct connection to 230V AC. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.	1002967
Number of different light outlets	1
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI 2
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Ambient temperature	25 °C
Maximum ambient temperature	30 °C
Rated standby power	0.5 W
Level of inrush current	10 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0.01
Lumen	1580/1650 lm
Colour temperature	3000/4000 Kelvin
Beam angle	90 °
Color	white
CRI	80

Light Source

916435		LXXBXX data	L70B50
		Service life	30000 h
		Light distribution	rotational symmetric
		Light outlet	direct
		Height	7.5 cm
		Diameter	20 cm
		Net weight	0.796 kg
		Gross weight	1.132 kg
		BIG WHITE Page	272