



## NOTAPO I

### Indoor recessed wall light 3000K white

Aluminium recessed wall light NOTAPO I WL. The invisibly installed LED emits its light indirectly onto the surface to be illuminated. This makes glare-free illumination of walkways and staircases possible, for example. The NOTAPO I recessed fitting is available with a white housing. An installation frame and a mounting box for installation in masonry are optionally available. This luminaire contains built-in LED lamps.

## TECHNICAL DATA

Item no.	1002979
IP Code	IP 20
Assembly	Recessed
Assembly details	Wall, Wall with Acc.
Secondary power / voltage	700 mA
Safety class	III
Wattage	2.2 W
Maximum ambient temperature	40 °C
Lumen	6 lm
Colour temperature	3000 Kelvin
Color	white
CRI	90
LXXBXX data	L70B50
Service life	35000 h
Light distribution	asymmetric
Light outlet	indirect
Width	3.6 cm
Height	10.5 cm
Depth	3.8 cm
Net weight	0.077 kg
Gross weight	0.117 kg
Shape of cut-out	square

Light Source

954799	
--------	---

Accessories

1007213	LED DRIVER , 10W, 700-mA, PHASE, incl. strain relief
1007216	LED driver 3W , 700mA incl. strain relief
1007229	LED driver 25W 150-700-mA DALI TOUCH
1002981	NOTAPO I and II WL , installation frame

Installation length	10 cm
Installation width	2.8 cm
Installation depth	5 cm
BIG WHITE Page	241