




ABRIDOR SENSOR

Outdoor LED surface-mounted wall light IP55 anthracite 3000/4000K

The aluminium luminaires in the ABRIDOR family provide solutions for the wall light and floor stand area. Thanks to its IP55 protection class, the luminaires are suitable for outdoor use. The electrical connection is made directly to the 230V mains power supply. The unusual lamp head means that the built-in LED has particularly wide light distribution.



TECHNICAL DATA

Item no.	1002990
Rotating or tilting	tiltable
IP Code	IP 54
Impact resistance class	IK 03
Impact resistance	0.35 Joule
Assembly	Surface
Assembly details	Wall
Primary nominal voltage	100-240V ~50/60Hz
Secondary power / voltage	300 mA
Safety class	I
Wattage	12 W
Minimum ambient temperature	-25 °C
Maximum ambient temperature	40 °C
Level of inrush current	5 A
Duration of inrush current	100 µs
Stroboscopic effect (SVM)	0.02
Lumen	950/980 lm
Colour temperature	3000/4000 Kelvin
Beam angle	100 °
Color	anthracite
CRI	80
LXXBXX data	L70B50

Light Source



Service life	30000 h
Length	14 cm
Height	16 cm
Depth	17.5 cm
Net weight	1.272 kg
Gross weight	1.545 kg
BIG WHITE Page	770