



SENSER 24


Indoor LED surface-mounted ceiling light round white 3000K

The flat SENSER wall and ceiling light made from aluminium is available in white and silver-grey, in a round or square version. The rigid Premium LED insert produces homogeneous base illumination over a wide area thanks to its extensive beam angle.

TECHNICAL DATA

Item no.	1003016
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Ceiling, Wall
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	15 W
Ambient temperature	25 °C
Operating efficiency (LOR)	0,7
Number of luminaires at LS B16A	61
Number of luminaires at LS C16A	61
Level of inrush current	10 A
Duration of inrush current	40 µs
Stroboscopic effect (SVM)	0.03
Lumen	1140 lm
Colour temperature	3000 Kelvin
Color	white

Light Source

916612		CRI	90
		UGR ≤	27
		LXXBXX data	L70B50
		Service life	48000 h
		Risk Group	1
		Height	3.5 cm
		Diameter	21.5 cm
		Net weight	0.513 kg
		Gross weight	0.607 kg
		BIG WHITE Page	419