




DINGILO

Indoor LED recessed ceiling light black 2700K tiltable


This should be your choice of recessed ceiling light if colour rendering is very important to you. With a CRI value of over 90, the DINGILO is extremely suitable for true-colour lighting of rooms.



TECHNICAL DATA

Item no.	1003036
Rotating or tilting	tiltable
IP Code	IP 20 / IP 44
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Primary nominal voltage	100-277V ~50/60Hz
Secondary power / voltage	200 mA
Safety class	II
Wattage	4.4 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Level of inrush current	13 A
Duration of inrush current	300 µs
Stroboscopic effect (SVM)	0
Lumen	330 lm
Colour temperature	2700 Kelvin
Beam angle	40 °
Color	black
CRI	90
LXXBXX data	L70B50

Light Source

916578		Service life	30000 h
		Light distribution	rotational symmetric
		Light outlet	direct
		Height	4 cm
		Diameter	8 cm
		Net weight	0.213 kg
		Gross weight	0.275 kg
		Installation depth	4 cm
		Installation diameter	6.8 cm