


I-PENDANT PRO DALI

Indoor LED pendant UGR<19 grey 3000K


With the I-PENDANT PRO DALI, which is available with several different light colours, we are providing a modern and space-saving solution for an efficient kind of basic lighting with the additional possibility of DALI control. The high degree of luminous flux provides a pleasant, homogeneous and glare-free lighting sensation. The electrical connection is made via the built-in LED power supply directly to a 100-240V mains power supply.



TECHNICAL DATA

Item no.	1003050
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	120-277V ~50/60Hz
Secondary power / voltage	1000 mA
Safety class	II
Wattage	43 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Network rated standby power	0.3 W
Level of inrush current	30 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0.02
Lumen	3750 lm
Colour temperature	3000 Kelvin
Beam angle	90 °
Color	grey
CRI	80
UGR ≤	19

Light Source

916402		LXXBXX data	L70B50
		Service life	30000 h
		Length	119.5 cm
		Width	29.5 cm
		Height	1.3 cm
		Pendant length	170 cm
		Net weight	5.083 kg
		Gross weight	6.151 kg
		BIG WHITE Page	289