




PANEL DALI

Indoor LED surface-mounted ceiling lights
1200x300mm grey 4000K


The PANEL DALI pendant, which is available in several different light colours, impresses with its ultra-flat design and powerful, dimmable LED modules. The aluminium frame is fitted with an acrylic glass cover which provides homogeneous and glare-free illumination. The built-in DALI-compatible operating device makes direct connection to a mains power supply of 100V - 240V possible.



TECHNICAL DATA

Item no.	1003055
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	120-277V ~50/60Hz
Secondary power / voltage	1000 mA
Safety class	I
Wattage	43 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Network rated standby power	0.3 W
Level of inrush current	30 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0.02
Lumen	3400 lm
Colour temperature	4000 Kelvin
Beam angle	90 °
Color	grey
CRI	80
UGR ≤	19

Light Source

916385		LXXBXX data	L70B50
		Service life	30000 h
		Length	119.5 cm
		Width	29.5 cm
		Height	5 cm
		Net weight	4.457 kg
		Gross weight	5.319 kg
		BIG WHITE Page	275