




NEW TRIA 68 I CS

Indoor LED recessed ceiling light black 2700K round

You get particularly pleasant, dimmable light for your rooms thanks to the integrated Premium LED in the NEW TRIA 68 I CS recessed ceiling light. Of course, there are many usage options for the luminaire. The NEW TRIA 68 I CS is particularly suitable as a spotlight for accent lighting. With a CRI value of greater than or equal to 80, the NEW TRIA 68 I CS is very suitable for true-colour lighting of sales or office premises. The anticipated service life of 40,000 hours makes the NEW TRIA 68 I CS sustainable and low-maintenance. A convenient ceiling cut-out with a standard core bit is possible, making installation easier.



TECHNICAL DATA

| | |
|----------------------------|-----------------------------|
| Item no. | 1003065 |
| IP Code | IP 20 |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | Leading edge, trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 500 mA |
| Safety class | II |
| Wattage | 11 W |
| Level of inrush current | 2 A |
| Duration of inrush current | 40 µs |
| Stroboscopic effect (SVM) | 0.02 |
| Lumen | 800 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 38 ° |
| Color | black |
| CRI | 80 |
| LXXBXX data | L70B50 |
| Service life | 40000 h |
| Risk Group | 1 |
| Height | 4.5 cm |

Light Source

| | |
|--------|---|
| 916320 |  |
|--------|---|

| | |
|-----------------------|----------|
| Diameter | 8.2 cm |
| Net weight | 0.27 kg |
| Gross weight | 0.322 kg |
| Shape of cut-out | round |
| Installation depth | 5 cm |
| Installation diameter | 6.8 cm |