




LED PANEL 600x600

Indoor LED recessed ceiling light white 3000K
UGR<19

The LED PANEL 600 comes in several different light colours for grid ceilings and provides a modern and space-saving solution for an efficient kind of base lighting. You achieve a pleasant, homogeneous and glare-free lighting sensation with this product, with an aperture angle of less than 19°.



TECHNICAL DATA

Item no.	1003083
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling, Ceiling with Acc.
Secondary power / voltage	1050 mA
Safety class	III
Wattage	35 W
Lumen	4000 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L70B50
Service life	50000 h
Light distribution	axis symmetric
Light outlet	direct
Risk Group	1
Length	59.5 cm
Width	59.5 cm
Height	0.9 cm
Net weight	2.973 kg

Light Source

916527	
--------	---

Accessories

158791	CEILING PLATE , for LED PANEL, I-VIDUAL and I-VIDUAL LED PANEL, white
1002425	LED driver MEDO 600 , dimmable DALI/1-10V
464804	LED DRIVER , 40W, 1050mA, triac dimmable
158799	SUSPENSION SET , for LED PANEL, I-VIDUAL and I-VIDUAL LED PANEL, steel wire and Y-wire suspension

Gross weight	3.841 kg
Shape of cut-out	square
Installation depth	5 cm