




PARA FLAC DALI

Indoor LED pendant black 4000K

The PARA FLAC DALI Indoor LED pendant light black 4000K with its special lighting attributes is ideal for a technical, industrial setting. With IP 65 protection class, it is protected against external influences. As it offers a high power consumption of 104 watts, the pendant light is perfect for hall lighting. The light made of aluminium and polycarbonate (PC) is also convincing in terms of quality. When will you test out the benefits of SLV's impressive indoor lights?



TECHNICAL DATA

| | |
|-----------------------------------|-------------------|
| Item no. | 1003107 |
| Number of different light outlets | 1 |
| Rotating or tilting | tiltable |
| IP Code | IP 65 |
| Impact resistance class | IK 02 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | DALI |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 1600 mA |
| Safety class | I |
| Wattage | 104 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Level of inrush current | 60 A |
| Stroboscopic effect (SVM) | 0.02 |
| Lumen | 12800 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 90 ° |
| Color | black |
| CRI | 80 |

Light Source

| | |
|--------|---|
| 916378 |  |
|--------|---|

Accessories

| | |
|---------|---------------------------------------|
| 1001692 | PARA FLAC , reflector cover |
| 1000918 | REFLECTOR , for PARA FLAC LED pendant |
| 228730 | CONNECTION BOX , 3-pin, IP68 |
| 1001691 | PARA FLAC , reflector |

| | |
|--------------------|----------------------|
| UGR \leq | 28 |
| LXXBXX data | L70B50 |
| Service life | 50000 h |
| Light distribution | rotational symmetric |
| Light outlet | direct |
| Risk Group | 1 |
| Height | 27.5 cm |
| Diameter | 32 cm |
| Net weight | 4.484 kg |
| Gross weight | 6.108 kg |