




PEMA® WL

outdoor LED surface-mounted wall light grey CCT switch 3000/4000K

The PEMA® WL LED wall light consists of lacquered aluminium and glass, which covers the LED light source. Thanks to its high protection class, the luminaire is suitable for outdoor use. The light colour can be switched between 3000K and 4000K during installation using the built-in CCT switch. Because of the built-in LED driver, the electrical connection of the luminaire, which is available in several colours, is made directly to the 230V mains supply.



TECHNICAL DATA

| | |
|-----------------------------|-------------------|
| Item no. | 1003454 |
| IP Code | IP 65 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Assembly | Surface |
| Assembly details | Wall |
| Number of through-wires | 10 |
| Primary nominal voltage | 100-277V ~50/60Hz |
| Secondary power / voltage | 350 mA |
| Safety class | I |
| Wattage | 14 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Level of inrush current | 6 A |
| Duration of inrush current | 25 µs |
| Stroboscopic effect (SVM) | 0.02 |
| Lumen | 1340/1420 lm |
| Colour temperature | 3000/4000 Kelvin |
| Color | grey |
| CRI | 80 |
| LXXBXX data | L70B50 |
| Service life | 30000 h |

Light Source

| | |
|--------|---|
| 916431 |  |
|--------|---|

| | |
|----------------|----------|
| Width | 28 cm |
| Height | 10 cm |
| Depth | 9 cm |
| Net weight | 1.189 kg |
| Gross weight | 1.331 kg |
| BIG WHITE Page | 759 |