




PEMA® WL

outdoor LED surface-mounted wall light grey CCT switch 3000/4000K

The PEMA® WL LED wall light consists of lacquered aluminium and glass, which covers the LED light source. Thanks to its high protection class, the luminaire is suitable for outdoor use. The light colour can be switched between 3000K and 4000K during installation using the built-in CCT switch. Because of the built-in LED driver, the electrical connection of the luminaire, which is available in several colours, is made directly to the 230V mains supply.



TECHNICAL DATA

Item no.	1003454
IP Code	IP 65
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Wall
Number of through-wires	10
Primary nominal voltage	100-277V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	14 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	6 A
Duration of inrush current	25 µs
Stroboscopic effect (SVM)	0.02
Lumen	1340/1420 lm
Colour temperature	3000/4000 Kelvin
Color	grey
CRI	80
LXXBXX data	L70B50
Service life	30000 h

Light Source

916431	
--------	---

Width	28 cm
Height	10 cm
Depth	9 cm
Net weight	1.189 kg
Gross weight	1.331 kg
BIG WHITE Page	759