




QUAD FRAME 9

indoor LED recessed wall light 3000K white

LED recessed wall light QUAD FRAME 9. The invisibly installed LED emits its light indirectly onto the surface to be illuminated. This makes glare-free illumination of walkways and staircases possible, for example. The QUAD FRAME 9 recessed fitting is available in white colour version. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.	1003466
Assembly	Recessed
Assembly details	Wall, Wall with Acc.
Primary nominal voltage	100-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	3 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	15 A
Duration of inrush current	300 µs
Stroboscopic effect (SVM)	0
Lumen	75 lm
Colour temperature	3000 Kelvin
Color	white
CRI	90
LXXBXX data	L70B50
Service life	30000 h
Risk Group	0
Width	9 cm
Height	9 cm
Depth	8 cm

Light Source

916565	
--------	---

Accessories

112781	MOUNTING BOX , for FRAME BASIC, FLAT FRAME BASIC, FLAT FRAME CURVE and FRAME CURVE
112780	FLUSH-MOUNTED , FRAME, for FRAME BASIC, FLAT FRAME BASIC, FLAT FRAME CURVE and FRAME CURVE

Net weight	0.383 kg
Gross weight	0.459 kg
Shape of cut-out	square
Installation length	7.2 cm
Installation width	8 cm
Installation depth	6.5 cm
BIG WHITE Page	240