




## MANA OUT WL

Wall-mounted light set grey/anthracite 11W 650lm  
3000K CRI80 60° Phase cut-off

Now also available with a shade in the fashionable material concrete: the dimmable MANA OUT WL wall light is designed with a high-performance LED for a warm white light (3000 K). Thanks to its IP65 protection class rating, this aluminium and concrete outdoor light is protected in any weather. The CRI of over 80 ensures natural colour reproduction. And thanks to the already integrated LED driver, a direct connection to a 220 volt supply is possible.



## TECHNICAL DATA

|                                   |                   |
|-----------------------------------|-------------------|
| Item no.                          | 1003470           |
| Number of different light outlets | 2                 |
| IP Code                           | IP 65             |
| Impact resistance class           | IK 02             |
| Impact resistance                 | 0.2 Joule         |
| Assembly                          | Surface           |
| Assembly details                  | Wall              |
| Dimmable                          | Yes               |
| Dimming technology                | trailing edge     |
| Primary nominal voltage           | 220-240V ~50/60Hz |
| Secondary power / voltage         | 500 mA            |
| Safety class                      | I                 |
| Wattage                           | 11 W              |
| Minimum ambient temperature       | -20 °C            |
| Maximum ambient temperature       | 45 °C             |
| Level of inrush current           | 12.4 A            |
| Duration of inrush current        | 7.2 µs            |
| Stroboscopic effect (SVM)         | 0.04              |
| Lumen                             | 650 lm            |
| Colour temperature                | 3000 Kelvin       |
| Beam angle                        | 60 °              |
| Color                             | grey              |

Light Source

|        |   |
|--------|---|
| 916573 |  |
|--------|---|

|                    |                   |
|--------------------|-------------------|
| CRI                | 80                |
| LXXBXX data        | L70B50            |
| Service life       | 30000 h           |
| Light distribution | axis symmetric    |
| Light outlet       | direct - indirect |
| Risk Group         | 1                 |
| Length             | 18.2 cm           |
| Width              | 16 cm             |
| Height             | 10.3 cm           |
| Net weight         | 2.67 kg           |
| Gross weight       | 3.317 kg          |
| BIG WHITE Page     | 721               |