




## OUT-BEAM FRAME CW

Outdoor LED wall and ceiling mounted light white 3000K

With the white OUT-BEAM FRAME CW, you have an outdoor surface-mounted light which is ideally suited for accentuating buildings. This light is intended for use in both residential and public areas. Thanks to the OUT-BEAM FRAME CW you can illuminate historical or modern buildings with wonderful effects. With an expected lifespan of 30,000 hours, the LED light is extremely sustainable and requires little maintenance.



## TECHNICAL DATA

Item no.	1003519
IP Code	IP 55
Impact resistance class	IK 03
Impact resistance	0.35 Joule
Assembly	Surface
Assembly details	Ceiling,Ground,Wall
Number of through-wires	10
Primary nominal voltage	100-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	3.5 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	15 A
Duration of inrush current	300 µs
Stroboscopic effect (SVM)	0
Lumen	60 lm
Colour temperature	3000 Kelvin
Beam angle	5 °
Color	white
CRI	80
LXXBXX data	L70B50

Light Source

916607	
--------	---

Service life	30000 h
Risk Group	1
Length	17.3 cm
Width	8.5 cm
Height	6.7 cm
Net weight	0.657 kg
Gross weight	0.781 kg
BIG WHITE Page	811