




## L-LINE OUT 50 FL POLE

Outdoor LED free-standing light horizontal anthracite  
CCT switch 3000/4000K

Whether in gardens, along the paths and driveways of residential buildings, hotels or restaurants - with its variety of lights, the L-LINE OUT family lights the way outdoors. Despite their individual differences, the individual members share a design vocabulary in L-shape, which stands out with its clear lines. And when it comes to lighting technology, there are no compromises: the choice of light colour (3000/4000K), which can be selected during the easy installation process, and IP protection class 65 are just some of the benefits of the L-LINE OUT.



## TECHNICAL DATA

|                                   |                   |
|-----------------------------------|-------------------|
| Item no.                          | 1003537           |
| Number of different light outlets | 1                 |
| IP Code                           | IP 65             |
| Impact resistance class           | IK 02             |
| Impact resistance                 | 0.2 Joule         |
| Assembly                          | Surface           |
| Assembly details                  | Ground            |
| Primary nominal voltage           | 220-240V ~50/60Hz |
| Secondary power / voltage         | 350 mA            |
| Safety class                      | I                 |
| Wattage                           | 7 W               |
| Minimum ambient temperature       | -20 °C            |
| Maximum ambient temperature       | 45 °C             |
| Level of inrush current           | 10 A              |
| Duration of inrush current        | 40 µs             |
| Stroboscopic effect (SVM)         | 0.08              |
| Lumen                             | 490/530 lm        |
| Colour temperature                | 3000/4000 Kelvin  |
| Color                             | anthracite        |
| CRI                               | 80                |
| LXXBXX data                       | L70B50            |
| Service life                      | 30000 h           |

Light Source

|        |   |
|--------|---|
| 916406 |  |
|--------|---|

Accessories

|        |                                 |
|--------|---------------------------------|
| 228730 | CONNECTION BOX ,<br>3-pin, IP68 |
|--------|---------------------------------|

|                |          |
|----------------|----------|
| Light outlet   | direct   |
| Risk Group     | 0        |
| Length         | 15 cm    |
| Width          | 10 cm    |
| Height         | 50 cm    |
| Net weight     | 2.023 kg |
| Gross weight   | 2.542 kg |
| BIG WHITE Page | 651      |