



NUMINOS® MOVE DL M

Indoor LED recessed ceiling light black/white 2700K
55° rotating and pivoting

The NUMINOS light system from SLV perfectly combines function, design and technology. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® MOVE DL M recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light has a power consumption of 17.55 watts, a luminous flux of 1600 lumens, a colour temperature of 2700 Kelvin and a high colour reproduction index of over 90. This means that simple installation is a mere formality. When will you choose SLV's modular variety?

TECHNICAL DATA

| | |
|-----------------------------------|-------------------------|
| Item no. | 1003560 |
| Number of different light outlets | 1 |
| Rotating or tilting | rotary Bar and tiltable |
| IP Code | IP 20 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Secondary power / voltage | 500 mA |
| Safety class | III |
| Wattage | 17.55 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Lumen | 1600 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 55 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 22 |
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Light distribution | rotational symmetric |

Light Source

| | |
|--------|---|
| 791800 |  |
|--------|---|

Accessories

| | |
|---------|--|
| 1004792 | NUMINOS® M , diffuser Frosted |
| 1004069 | LED driver , 29W 500mA |
| 1004064 | LED driver , 21-29.5W 500/600/700mA |
| 1006459 | LED bridge driver , 42W, 500mA for NUMINOS®, including radio interface for RF module, DALI |
| 1006143 | Numinos® M Reducing ring , round 240/120mm black |
| 1004054 | LED driver , 20W 500mA PHASE |
| 1006146 | Numinos® M Reducing ring , square 240/120mm white |
| 1006454 | RF module Casambi for LED bridge driver , single colour |
| 1006144 | Numinos® M Reducing ring , round 240/120mm white |
| 1004793 | NUMINOS® M , diffuser Wabe |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour |
| 1006145 | Numinos® M Reducing ring , square 240/120mm black |
| 1004790 | NUMINOS® M , diffuser Ellipse |
| 1004791 | NUMINOS® M , diffuser Prisma |

| | |
|-----------------------|---------|
| Light outlet | direct |
| Risk Group | 1 |
| Height | 9 cm |
| Diameter | 13.5 cm |
| Net weight | 0.39 kg |
| Gross weight | 0.45 kg |
| Shape of cut-out | round |
| Installation depth | 10 cm |
| Installation diameter | 12 cm |
| BIG WHITE Page | 87 |