



NUMINOS® MOVE DL XL

Indoor LED recessed ceiling light white/black 4000K
55° rotating and pivoting

NUMINOS is the best possible coordinated light system from SLV that combines function, design and technology. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® MOVE DL XL recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light has a power consumption of 37.4 watts, a luminous flux of 3600 lumens, a colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. This means that simple installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.

TECHNICAL DATA

| | |
|-----------------------------------|-------------------------|
| Item no. | 1003763 |
| Number of different light outlets | 1 |
| Rotating or tilting | rotary Bar and tiltable |
| IP Code | IP 20 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Secondary power / voltage | 1050 mA |
| Safety class | III |
| Wattage | 37.4 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Lumen | 3600 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 55 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 25 |
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Light distribution | rotational symmetric |

Light Source

| | |
|--------|---|
| 791850 |  |
|--------|---|

Accessories

| | |
|---------|---|
| 1006152 | Numinos® XL Reducing ring , round 240/180mm white |
| 1006151 | Numinos® XL Reducing ring , round 240/180mm black |
| 1004800 | NUMINOS® XL , diffuser Frosted |
| 1004071 | LED driver 4.2-50W 1050mA DALI |
| 1006454 | RF module Casambi for LED bridge driver , single colour |
| 1006154 | Numinos® XL Reducing ring , square 240/180mm white |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour |
| 1004798 | NUMINOS® XL , diffuser Ellipse |
| 1006153 | Numinos® XL Reducing ring , square 240/180mm black |
| 1004059 | LED driverm 40W multi mA |
| 1006461 | LED bridge driver , 42W, 1050mA for NUMINOS®, including radio interface for RF module, DALI |
| 1004066 | LED driver , 28-40W 1000mA PHASE |
| 1004801 | NUMINOS® XL , diffuser Wabe |
| 1004799 | NUMINOS® XL , diffuser Prisma |

| | |
|-----------------------|---------|
| Light outlet | direct |
| Risk Group | 1 |
| Height | 11.8 cm |
| Diameter | 19 cm |
| Net weight | 0.7 kg |
| Gross weight | 0.89 kg |
| Shape of cut-out | round |
| Installation depth | 13 cm |
| Installation diameter | 17.5 cm |
| BIG WHITE Page | 87 |