



## NUMINOS® DL M

Indoor LED recessed ceiling light black/white 2700K 40°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. The various downlights and spotlights make a thousand lighting design options possible. Also with the NUMINOS® DL M recessed ceiling light, which convinces with the best workmanship and lighting quality. In this way, you can create unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light convinces with a power consumption of 17.55 watts, luminous flux of 1600 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When will you choose SLV's modular variety?

## TECHNICAL DATA

Item no.	1003845
Number of different light outlets	1
IP Code	IP 20 / IP 44
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	500 mA
Safety class	III
Wattage	17.55 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	1600 lm
Colour temperature	2700 Kelvin
Beam angle	40 °
Color	black
CRI	90
UGR ≤	19.4
LXXBXX data	L80B50
Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct

## Light Source

791800	
--------	---

## Accessories

1004792	NUMINOS® M , diffuser Frosted
1004069	LED driver , 29W 500mA
1004064	LED driver , 21-29.5W 500/600/700mA
1006459	LED bridge driver , 42W, 500mA for NUMINOS®, including radio interface for RF module, DALI
1004054	LED driver , 20W 500mA PHASE
1006139	Numinos® S Reducing ring , round 160/100mm black
1006454	RF module Casambi for LED bridge driver , single colour
1004793	NUMINOS® M , diffuser Wabe
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1006140	Numinos® S Reducing ring , round 160/100mm white
1006142	Numinos® S Reducing ring , square 160/100mm white
1004790	NUMINOS® M , diffuser Ellipse
1004791	NUMINOS® M , diffuser Prisma
1006141	Numinos® S Reducing ring , square 160/100mm black

Risk Group	1
Height	6.8 cm
Diameter	10.5 cm
Net weight	0.24 kg
Gross weight	0.28 kg
Shape of cut-out	round
Installation depth	7.5 cm
Installation diameter	9 cm
BIG WHITE Page	87