



## NUMINOS® DL M

Indoor LED recessed ceiling light black/white 3000K 20°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With a variety of downlights and spotlights, you provide a thousand lighting design options. This also includes NUMINOS® DL M, which impresses as a recessed ceiling light with the best workmanship and lighting quality. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light can convince with a power consumption of 17.55 watts, luminous flux of 1600 lumens, colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?

## TECHNICAL DATA

|                                   |                      |
|-----------------------------------|----------------------|
| Item no.                          | 1003866              |
| Number of different light outlets | 1                    |
| IP Code                           | IP 20 / IP 44        |
| Impact resistance class           | IK 02                |
| Impact resistance                 | 0.2 Joule            |
| Assembly                          | Recessed             |
| Assembly details                  | Ceiling              |
| Secondary power / voltage         | 500 mA               |
| Safety class                      | III                  |
| Wattage                           | 17.55 W              |
| Minimum ambient temperature       | -20 °C               |
| Maximum ambient temperature       | 40 °C                |
| Lumen                             | 1600 lm              |
| Colour temperature                | 3000 Kelvin          |
| Beam angle                        | 20 °                 |
| Color                             | black                |
| CRI                               | 90                   |
| UGR ≤                             | 22                   |
| LXXBXX data                       | L80B50               |
| Service life                      | 50000 h              |
| Light distribution                | rotational symmetric |
| Light outlet                      | direct               |

## Light Source

|        |   |
|--------|---|
| 791822 |  |
|--------|---|

## Accessories

|         |  |
|---------|--|
| 1004792 | NUMINOS® M , diffuser Frosted  |
| 1004069 | LED driver , 29W 500mA   |
| 1004064 | LED driver , 21-29.5W 500/600/700mA  |
| 1006459 | LED bridge driver , 42W, 500mA for NUMINOS®, including radio interface for RF module, DALI |
| 1004054 | LED driver , 20W 500mA PHASE   |
| 1006139 | Numinos® S Reducing ring , round 160/100mm black   |
| 1006454 | RF module Casambi for LED bridge driver , single colour                                    |
| 1004793 | NUMINOS® M , diffuser Wabe   |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour                                |
| 1006140 | Numinos® S Reducing ring , round 160/100mm white   |
| 1006142 | Numinos® S Reducing ring , square 160/100mm white  |
| 1004790 | NUMINOS® M , diffuser Ellipse  |
| 1004791 | NUMINOS® M , diffuser Prisma   |
| 1006141 | Numinos® S Reducing ring , square 160/100mm black  |

|                       |         |
|-----------------------|---------|
| Risk Group            | 1       |
| Height                | 6.8 cm  |
| Diameter              | 10.5 cm |
| Net weight            | 0.24 kg |
| Gross weight          | 0.28 kg |
| Shape of cut-out      | round   |
| Installation depth    | 7.5 cm  |
| Installation diameter | 9 cm    |
| BIG WHITE Page        | 87      |