



NUMINOS® DL M

Indoor LED recessed ceiling light black/chrome 3000K 40°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With different downlights and spotlights, you provide a thousand lighting design possibilities. Like with the NUMINOS® DL M recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light convinces with a power consumption of 17.55 watts, luminous flux of 1550 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.

TECHNICAL DATA

| | |
|-----------------------------------|----------------------|
| Item no. | 1003870 |
| Number of different light outlets | 1 |
| IP Code | IP 20 / IP 44 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Secondary power / voltage | 500 mA |
| Safety class | III |
| Wattage | 17.55 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Lumen | 1550 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 40 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 19 |
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Light distribution | rotational symmetric |
| Light outlet | direct |

Light Source

| | |
|--------|---|
| 791822 |  |
|--------|---|

Accessories

| | |
|---------|--|
| 1004792 | NUMINOS® M , diffuser Frosted |
| 1004069 | LED driver , 29W 500mA |
| 1004064 | LED driver , 21-29.5W 500/600/700mA |
| 1006459 | LED bridge driver , 42W, 500mA for NUMINOS®, including radio interface for RF module, DALI |
| 1004054 | LED driver , 20W 500mA PHASE |
| 1006139 | Numinos® S Reducing ring , round 160/100mm black |
| 1006454 | RF module Casambi for LED bridge driver , single colour |
| 1004793 | NUMINOS® M , diffuser Wabe |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour |
| 1006140 | Numinos® S Reducing ring , round 160/100mm white |
| 1006142 | Numinos® S Reducing ring , square 160/100mm white |
| 1004790 | NUMINOS® M , diffuser Ellipse |
| 1004791 | NUMINOS® M , diffuser Prisma |
| 1006141 | Numinos® S Reducing ring , square 160/100mm black |

| | |
|-----------------------|---------|
| Risk Group | 1 |
| Height | 6.8 cm |
| Diameter | 10.5 cm |
| Net weight | 0.24 kg |
| Gross weight | 0.28 kg |
| Shape of cut-out | round |
| Installation depth | 7.5 cm |
| Installation diameter | 9 cm |
| BIG WHITE Page | 87 |