



NUMINOS® DL L

Indoor LED recessed ceiling light black/white 2700K
20° gimballed, rotating and pivoting

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. The diverse downlights and spotlights make a thousand lighting design options possible. Also with the NUMINOS® DL L recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light can convince with a power consumption of 25.41 watts, luminous flux of 2250 lumens, colour temperature of 2700 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When will you choose SLV's modular variety?

TECHNICAL DATA

Item no.	1003914
Number of different light outlets	1
IP Code	IP 20 / IP 44
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	700 mA
Safety class	III
Wattage	25.41 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	2250 lm
Colour temperature	2700 Kelvin
Beam angle	20 °
Color	black
CRI	90
UGR ≤	19
LXXBXX data	L80B50
Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct

Light Source

791800	
--------	---

Accessories

1004062	LED driver , 21-29.5W 500/600/700mA for Numi- nos Downlight Serie
1004795	NUMINOS® L , diffuser Prisma
1004796	NUMINOS® L , diffuser Frosted
1006143	Numinos® M Reducing ring , round 240/120mm black
1006460	LED bridge driver , 42W, 700mA for NUMINOS®, including radio interface for RF module, DALI
1004794	NUMINOS® L , diffuser Ellipse
1006146	Numinos® M Reducing ring , square 240/120mm white
1006454	RF module Casambi for LED bridge driver , single colour
1006144	Numinos® M Reducing ring , round 240/120mm white
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1004070	LED driver , 40W 700mA DALI
1006145	Numinos® M Reducing ring , square 240/120mm black
1004797	NUMINOS® L , diffuser Wabe
1004065	LED driver , 30W 700mA

Risk Group	1
Height	8.5 cm
Diameter	13 cm
Net weight	0.465 kg
Gross weight	0.525 kg
Shape of cut-out	round
Installation depth	9 cm
Installation diameter	11.7 cm
BIG WHITE Page	87