



NUMINOS® DL L

Indoor LED recessed ceiling light black/black 4000K 40°

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Also with the NUMINOS® DL L recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light has a power consumption of 25.41 watts, a luminous flux of 2350 lumens, a colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.

TECHNICAL DATA

| | |
|-----------------------------------|----------------------|
| Item no. | 1003964 |
| Number of different light outlets | 1 |
| IP Code | IP 20 / IP 44 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Secondary power / voltage | 700 mA |
| Safety class | III |
| Wattage | 25.41 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Lumen | 2350 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 40 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 22 |
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Light distribution | rotational symmetric |
| Light outlet | direct |

Light Source

| | |
|--------|---|
| 791825 |  |
|--------|---|

Accessories

| | |
|---------|---|
| 1004062 | LED driver , 21-29.5W 500/600/700mA for Numinos Downlight Serie |
| 1004795 | NUMINOS® L , diffuser Prisma |
| 1004796 | NUMINOS® L , diffuser Frosted |
| 1006143 | Numinos® M Reducing ring , round 240/120mm black |
| 1006460 | LED bridge driver , 42W, 700mA for NUMINOS®, including radio interface for RF module, DALI |
| 1004794 | NUMINOS® L , diffuser Ellipse |
| 1006146 | Numinos® M Reducing ring , square 240/120mm white |
| 1006454 | RF module Casambi for LED bridge driver , single colour |
| 1006144 | Numinos® M Reducing ring , round 240/120mm white |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour |
| 1004070 | LED driver , 40W 700mA DALI |
| 1006145 | Numinos® M Reducing ring , square 240/120mm black |
| 1004797 | NUMINOS® L , diffuser Wabe |
| 1004065 | LED driver , 30W 700mA |

| | |
|-----------------------|----------|
| Risk Group | 1 |
| Height | 8.5 cm |
| Diameter | 13 cm |
| Net weight | 0.465 kg |
| Gross weight | 0.525 kg |
| Shape of cut-out | round |
| Installation depth | 9 cm |
| Installation diameter | 11.7 cm |
| BIG WHITE Page | 87 |