



NUMINOS® DL XL

Indoor LED recessed ceiling light black/black 3000K 20°

NUMINOS is the perfectly coordinated light system from SLV that combines function, design and technology. With a variety of downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINOS® DL XL recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light has a power consumption of 37.4 watts, a luminous flux of 3300 lumens, a colour temperature of 3000 Kelvin and a good colour reproduction index of over 90. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.

TECHNICAL DATA

| | |
|-----------------------------------|----------------------|
| Item no. | 1004009 |
| Number of different light outlets | 1 |
| IP Code | IP 20 / IP 44 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Secondary power / voltage | 1050 mA |
| Safety class | III |
| Wattage | 37.4 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Lumen | 3300 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 20 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 22 |
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Light distribution | rotational symmetric |
| Light outlet | direct |

Light Source

| | |
|--------|---|
| 791823 |  |
|--------|---|

Accessories

| | |
|---------|---|
| 1006148 | Numinos® L Reducing ring , round 240/150mm white |
| 1006149 | Numinos® L Reducing ring , square 240/150mm black |
| 1004800 | NUMINOS® XL , diffuser Frosted |
| 1004071 | LED driver 4.2-50W 1050mA DALI |
| 1006150 | Numinos® L Reducing ring , square 240/150mm white |
| 1006454 | RF module Casambi for LED bridge driver , single colour |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour |
| 1006147 | Numinos® L Reducing ring , round 240/150mm black |
| 1004798 | NUMINOS® XL , diffuser Ellipse |
| 1004059 | LED driverm 40W multi mA |
| 1006461 | LED bridge driver , 42W, 1050mA for NUMINOS®, including radio interface for RF module, DALI |
| 1004066 | LED driver , 28-40W 1000mA PHASE |
| 1004801 | NUMINOS® XL , diffuser Wabe |
| 1004799 | NUMINOS® XL , diffuser Prisma |

| | |
|-----------------------|----------|
| Risk Group | 1 |
| Height | 10.8 cm |
| Diameter | 16 cm |
| Net weight | 0.699 kg |
| Gross weight | 0.856 kg |
| Shape of cut-out | round |
| Installation depth | 11.5 cm |
| Installation diameter | 14.5 cm |
| BIG WHITE Page | 87 |