### **Specialist • Lighting • Vendor**








# NUMINOS® SPOT PHASES

## Indoor LED recessed ceiling light black/black 3000K $60^{\circ}$

NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NU-MINOS® SPOT PHASE S indoor ceiling-mounted light LE-D, which convinces with the best workmanship and lighting quality. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 1020 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When do you choose NUMINOS ® from SLV?



#### **TECHNICAL DATA**

Item no.	1004108
Rotating or tilting	rotary Bar and tiltable
Assembly	Surface
Assembly details	Ceiling, Wall
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	250 mA
Safety class	I
Wattage	10.42 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	88
Number of luminaires at LS C16A	88
Level of inrush current	8.5 A
Duration of inrush current	60 µs
Lumen	1020 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	black
CRI	90
UGR≤	19

## Specialist • Lighting • Vendor



#### **Light Source**

791815	A F
Accessories	
1006167	NUMINOS® S , white front ring

LXXBXX data	L80B50
Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Length	16.2 cm
Height	14.5 cm
Diameter	6.5 cm
Net weight	0.58 kg
Gross weight	0.87 kg
BIG WHITE Page	100