



## NUMINOS® CL PHASE S

Indoor LED surface ceiling light black/black 3000K 24°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. The diverse downlights and spotlights make a thousand lighting design options possible. Also with the NUMINOS® CL PHASE S indoor ceiling-mounted light LED, which convinces with the best workmanship and lighting quality. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 1020 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.

## TECHNICAL DATA

Item no.	1004130
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	250 mA
Safety class	I
Wattage	10.42 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	88
Number of luminaires at LS C16A	88
Level of inrush current	8.5 A
Duration of inrush current	60 µs
Lumen	1020 lm
Colour temperature	3000 Kelvin
Beam angle	24 °
Color	black
CRI	90
UGR ≤	13
LXXBXX data	L80B50

Light Source

791815	
--------	---

Accessories

1006167	NUMINOS® S , white front ring
---------	-------------------------------

Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Height	16.2 cm
Diameter	6.5 cm
Net weight	0.425 kg
Gross weight	0.65 kg
BIG WHITE Page	104